

iCHAIR MC3

1.612




Authorised client weight
160 kg (incl. additional load)

With seat lift CODE 27
150 kg (incl. additional load)





Service-friendly
Simple battery maintenance
thanks to pull-out battery box



300 mm lift



Long-life LED light



All-wheel suspension

Design meets function

COST EFFECTIVENESS

- efficiency thanks to simple maintenance and a high degree of ease in servicing
- little need for repairs as a result of the use of high-end and long-life components
- the modular design of the iChair family means great compatibility of components
- multiple settings allow for individual adjustment
- optimal user size limits make reuse simpler

THERAPEUTIC BENEFITS

- ideal for maintaining mobility at home, at the work station and around the office
- effective pressure relief and relaxed positioning for long periods of sitting are facilitated by the large, electrically operated adjusting areas
- various seat units for corresponding to individual needs
- ideal ride comfort for long distances thanks to the all-wheel suspension as standard
- the stable 300 mm seat lift supports the mobility and social integration of the user

APPLICATIONS

- for both indoors and out
- for permanent and all-day use for independent mobility, even for more advanced functional disorders
- for working and active people who require a wheelchair for numerous different everyday situations
- suitable for outdoor use thanks to large tyres and all-wheel suspension as standard
- interior spaces are mastered with ease thanks to the compact design, high manoeuvrability and optional seat lift

ORDER

QUOTATION

CUSTOM-MADE VERSION

Please fax your completed order form to: +49 (0) 5733 922 9311 Customer service: +49 (0) 5733 922 311

Invoice address / customer no:
Delivery address:
Consignment / remarks:

MEYRA®



Authorised client weight
160 kg (incl. additional load)

With seat elevation CODE 27
150 kg (incl. additional load)

iChair mc3 1.612

All prices exclude VAT at the statutory rate. Valid from 01.01.2018 to 31.12.2018.
Our general terms and conditions apply, which can be found on www.meyra.de/en/gtc.



Technical data

Seat width ^{1) 2)}	380 - 650
Seat depth ²⁾	400 - 560/400 - 560/500/480 - 530
Back rest height ²⁾	450 - 500 / 530 - 570 / 640 / 640
Shank length ²⁾	280 - 430/350 - 500/350 - 500/350 - 500
Armrest height ^{2) 7)}	240 - 350/180 - 290/140 - 250/18 - 290
Front seat height ²⁾	460 - 520/530 - 590/580 - 640/610 - 670
Length with footrests	1,170
Length without footrests	870

Width ready to go ³⁾	630
Height without headrest ³⁾	970 - 1,140
Transport dim. length	870
Transport dim. height min.	590
Front wheel size	260 x 70 (10")
Rear wheel size	356 x 75 (14")
Max. obstacle height	70
Turning radius	900
Range with batteries 38 Ah (5h), 45 Ah (20h)	25 - 30
Range with batteries 63 Ah (5h), 73 Ah (20h)	35 - 40



Please tick your choice in the boxes

Standard version: In case you do not make another selection we will generally deliver the standard version.**Technical data**

Empty transport weight min. ⁴⁾	108
Client weight max. ⁸⁾	160
Permitted overall weight	320
Additional loading max.	10

1) See category 01 seat width

2) Seat systems belt / ErgoSeat / ERGOSTAR / RECARO

3) Seat systems belt / ErgoSeat

4) Without legrests and without armrests

5) Under test conditions 6 / 10 km/h with battery 73 Ah (20h)

6) See category 00 chassis/motorisation

7) with armrest CODE 106

8) Advise: 150 kg at CODE 27

**Dimensions in mm (1 inch = 25,4 mm), Weights in kg (1 pd = 0,45 kg),
Speed in km/h (1 mph = 1,61 km/h), Tolerance ± 10 mm / 0,39 inch The
specifications are subject to constructional changes.**

PERFORMANCE

Driving speeds	6 / 10
Motor performance W, 6/10 km/h	2 x 220 / 2 x 300
Range with batteries 43 Ah(5h) / 50 Ah(20h) max. in km ⁶⁾	25 - 30
Range with batteries 63 Ah (5h), 73 Ah (20h) max. in km ⁶⁾	35 - 40
Permitted gradient	15 %
Type of steering	indirect
Electric tilt-in-space	-2° to 33°
Mechanical tilt-in-space	0° to 10°
Back angle electric	-10° to 50°
Back angle mechanical	-10° to 30°
Seat elevation electric	30